



M10N

Enterprise-Grade Rugged Tablet

- New generation Intel® N150 processor
- 10.1" FHD display with brightness up to 1000 nits
- Dual-band Wi-Fi 6, BT 5.2 and 4G connectivity
- Supports 1D/2D barcode reader, NFC and fingerprint module
- Extension interface (3 choose 1, RJ45, RS232, USB Type-A)
- MIL-STD-810H and IP65 certified













Durability	 MIL-STD 810H certified 4ft, 26 drops (each side, edge, and corner) IP65 certified ±8kV contact discharge, ±10kV air discharge 	Security	Integrated TPM2.0Fingerprint scannerOptional HF-RFID (NFC) reader
Operating System	Windows 11 Home Optional Windows 11 Pro/IOT	Data Capture	Optional 1D/2D barcode reader
Processor	· Intel N150 (6MB cache, up to 3.6 GHz, 4 cores, 4 threads, TDP 6W)	I/O Interface	 Micro SD card x1 SIM card x1 USB 3.2 Gen 1 (Type-A) x1
Graphics	· Intel® Graphics		 USB 3.2 Gen 1 (Type-C) x1 3.5 mm audio jack x1 HDMI 2.0a mini x1
Memory	8GB LPDDR5 on board Optional 16GB LPDDR5		5.5 mm DC in jack x1 12–pin Pogo Pin x1 (Charge&USB)
Storage	128GB EMMC Optional 256GB eMMC	Battery & Charging	 Optional RS232 Optional USB 2.0 Gen 1 (Type-A) x1 Default 10/100/1000M Ethernet (USB 2.0) x1
Display	 10.1", FHD (1200x1920), 1000 nits 10-point capacitive touch screen, supports glove touch mode 	Environment	· Li-ion battery, 7.6V, 5000mAh, 6h30min
Audio	 Integrated 1W speaker Integrated microphone Class K 		 RTC 3V/1mAh on board Optional separate RTC AC adapter: 100–240V, 50Hz–60Hz, 48W (12V/4A)
Camera	MF 5.0 MP front camera AF 8.0 MP rear camera	Dimension	 Operating temperature: -20°C to 60°C (-4°F to 140°F) Storage temperature: -30°C to 70°C (-22°F to 158°F) Humidity: 95% (Non-condensing)
Keyboard & Input	· 5 buttons (user-definable key x1)	Weight	· 274.9 mm (L) × 188.7 mm (W) × 22.2 mm (H)
		Accessories	· 1140g
& Connectivity	· Intel® Wi–Fi 6 (802.11 ax) · Bluetooth® 5.2 · 4G LTE	Warranty	 Standard: Adapter, Hand strap Optional: Docking charger, Quad charging dock, Vehicle mount, Removable battery
	LTE-FDD: B1/3/5/7/8/20/28 LTE-TDD: B38/40/41 WCDMA:B1/5/8		One-year limited warranty standard
	GSM: / Optional 4G LTE LTE-FDD: B2/4/5/12/13/17/18/25/26 LTE-TDD: B4/4/5/12/13/17/18/25/26	Battery life data is provid Actual results may vary depe Certified to MIL-STD-810	representative for feature availability. ed by Emdoor's laboratory. Default test conditions: 300 nits display brightness, 30 cm/70 dB sound le ending on test environments and methods. OH and IP standards. For specific test items and methods, please refer to the latest official test report ight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and

- 5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

ACCESSORIES

Standard



Adapter (US)



Adapter (EU)

CDMA&EVDO: BC0/BC1

GSM: 850/1900 Optional 4G LTE LTE-FDD: B2/4/5/7/8/28

LTE-TDD: B40 WCDMA: B2/5/8 GSM: 850/900/1900

· GPS module



Hand Strap

Optional









Docking Charger

Quad Charging Dock

Battery

CONTACT US

Shenzhen Emdoor Information Co., Ltd. (Stock Code: 001314) Tel: (+86) 400-830-4882 Email: inquiry@onerugged.com

Address: Emdoor Building, No.8 Guangke 1st Road, Pingshan District, Shenzhen Web: www.onerugged.com

