



V10T

Enterprise-Grade Rugged Tablet

- Equipped with Quad-core Intel JASPER LAKE N5100 processor
- 4G LTE, dual-band Wi-Fi and Bluetooth 5.1 connectivity
- IP65 dustproof and waterproof
- 10.1-inch screen, 1000cd/m² high brightness
- Supports the battery-free mode, and optional 7.4V/1000mAh capacity battery
- Supports USB/DB9/LAN/CAN and other interface extensions




Durability	<ul style="list-style-type: none"> MIL-STD 810H certified IP65 compliant ±8kV contact discharge, ±15kV air discharge
Operating System	<ul style="list-style-type: none"> Android 12 option Android 12 GMS
Processor	<ul style="list-style-type: none"> MT6789 (2x2.2Ghz Cortex-A76, 6x 2Ghz Corex-A55)
Graphics	<ul style="list-style-type: none"> Mali-G57 MC2
Memory	<ul style="list-style-type: none"> LPDDR4X-4266 (4GB)
Storage	<ul style="list-style-type: none"> UFS (64G)
Display	<ul style="list-style-type: none"> 10.1 inch, HD (800 x 1280), 1000 Nits 10 point capacitive touch screen
Audio	<ul style="list-style-type: none"> 2.5W/4Ω Speaker x 1 MIC x 1
Keyboard & Input	<ul style="list-style-type: none"> 5 buttons (4 user-definable key)
Network & Connectivity	<ul style="list-style-type: none"> WiFi 5 Dual-band (2.4G/5G) Bluetooth 5.2 4G LTE Cat 4 GSM : 2+3+5+8 WCDMA : 1+2+5+8 TD-S : 34+39 TDD : 38+39+40+41N(2535mhz~2655mhz) FDD : 1+2+3+4+5+7+8+17+20+28a+28b GNSS module
Data Capture	<ul style="list-style-type: none"> Option NFC 13.56MHZ reader Support protocols : ISO15693 , ISO14443 A , ISO14443B

I/O Interface	<ul style="list-style-type: none"> MICRO-SIM x 1 USB2.0 (USB_A) x 1 M12-8 (Input: 12V) PORT1 M12-12 (RJ45) Option M12-12 (100Mbps Ethernet RJ45) x 1 PORT2 M12-12 (RS232+RS485) Option M12-12 (RS232 x 1 + RS485 x 1) Option M12-12 (RS232 x 2) PORT3 M12-12 (USB2.0) Option M12-12 (USB2.0 x 3) Option M12-12 (USB2.0 x 2 + CAN x 1)
Battery & Charging	<ul style="list-style-type: none"> 3.7V/2000mAh Option Battery Li-Ion, 3.7V, 2000mAh M12-8 (Input:12V) RTC
Environment	<ul style="list-style-type: none"> Operating temperature: <ul style="list-style-type: none"> -20°C to 60°C (NO battery) -10°C to 60°C (battery) Storage temperature: -30°C to 70°C Humidity: 95% (Non-Condensing)
Dimension	<ul style="list-style-type: none"> 264.5 mm (L) × 184.1 mm (W) × 23.0 mm (H)
Weight	<ul style="list-style-type: none"> 824g
Accessories	<ul style="list-style-type: none"> Standard: WiFi Ext Ant, GNSS Ext Ant (3m), M12-8 to DC Cable, 4G Ext Ant Optional: PWR12V/4A DC (Car), ADP12V4ADC (EU), Power Cable, PWR MODULE, M12 to USB Cable, M12 to RJ45 Cable, M12 to RS232 + RS485 Cable, M12 to RS232 × 2 Cable, FULL Cable, Mount Parts
Warranty	<ul style="list-style-type: none"> One-year limited warranty standard

1. Please contact your sales representative for feature availability.
2. Battery life data is provided by Emdoor's laboratory. Default test conditions: 300 nits display brightness, 30 cm/70 dB sound level. Actual results may vary depending on test environments and methods.
3. Certified to MIL-STD-810H and IP standards. For specific test items and methods, please refer to the latest official test report.
4. Body dimensions and weight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and manufacturing processes.
5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

ACCESSORIES

Standard



Optional

PWR12V/4A DC (Car)	ADP12V4ADC (EU)	Power Cable (1.2m)	Power Cable (6m)	PWR MODULE (9-36V)
PWR MODULE (20-80V)	M12 to USB Cable (Straight Plug)	M12 to USB Cable (Angled Plug)	M12 to RJ45 Cable (Straight Plug)	M12 to RJ45 Cable (Angled Plug)
M12 to RS232 +RS485 Cable (Straight Plug)	M12 to RS232 +RS485 Cable (Angled Plug)	M12 to RS232 x 2 cable (Straight Plug)	FULL Cable (1.2m)	Mount Parts

CONTACT US

Shenzhen Emdoor Information Co., Ltd. (Stock Code: 001314)

Tel: (+86) 400-830-4882

Web: www.onerugged.com

Email: inquiry@onerugged.com

Address: Emdoor Building, No.8 Guangke 1st Road, Pingshan District, Shenzhen

